

# Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB04/005459

International filing date: 30 December 2004 (30.12.2004)

Document type: Certified copy of priority document

Document details: Country/Office: GB  
Number: 0400148.3  
Filing date: 06 January 2004 (06.01.2004)

Date of receipt at the International Bureau: 25 February 2005 (25.02.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland  
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



PCT/GB2004/005459.



INVESTOR IN PEOPLE


The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

*Stephen Hordley*


Dated

11 February 2005



—  
—  
—  
—

Patents Form 1/77

Patents Act 1977  
(Rule 16)06JAN04 EPO 346-1 010002  
F01/7700 0.10-0400148.3 NONE**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1. Your reference **jac.3186.uk.ja.d**
2. Patent application number  
(The Patent Office will fill in this part) **0400148.3** **- 6 JAN 2004**
3. Full name, address and postcode of the or of each applicant (underline all surnames)  
  
Patents ADP number (if you know it)  
  
If the applicant is a corporate body, give the country/state of its incorporation
- Calico Jack Ltd  
Argyll House  
Marketgait  
DUNDEE  
DD1 1QP  
8718546001  
UK**
4. Title of the invention **Dynamic modularity in flexible, persistent agents**
5. Name of your agent (if you have one)  
  
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)
- Kennedys Patent Agency Limited  
Floor 5, Queens House  
29 St Vincent Place  
Glasgow  
G1 2DT**
- Patents ADP number (if you know it) **08058240002**
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number
- | Country | Priority application number (if you know it) | Date of filing (day / month / year) |
|---------|--|-------------------------------------|
|         |  |                                     |
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application
- | Number of earlier application | Date of filing (day / month / year) |
|-------------------------------|-------------------------------------|
|                               |                                     |
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if
- a) any applicant named in part 3 is not an inventor, or  
b) there is an inventor who is not named as an applicant, or  
c) any named applicant is a corporate body.  
See note (d))
- Yes**

Patents Form 1/77

**Patents Form 1/77**

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

25

Claim(s)

Abstract

Drawing(s)

5 only

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

KENNEDYS

Date

6 January 2004

12. Name and daytime telephone number of person to contact in the United Kingdom

Jim Adams

Tel: 0141 226 6826

**Warning**

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

**Notes**

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

**Patents Form 1/77**

1 Dynamic Modularity in Flexible, Persistent Agents

2

3 The present invention relates to the dynamic deployment  
4 of functionality in software agents, in particular, a  
5 dynamic modular architecture for the agent that supports  
6 deployment of functionality that is not anticipated when  
7 the agent is instantiated.

8

9 Agents represent a means of representing a user in the  
10 electronic world, bringing together all the various  
11 functions that the user wants to perform in that  
12 electronic world, including:

- 13 • the transient, anonymous presence of an online search;
- 14 • persistent occasional presence of online shopping at a
- 15 particular store;
- 16 • persistent passive presence of directed marking;
- 17 • persistent though temporary realtime presence in an
- 18 online game;
- 19 and many more.

20

21 US Patent Application Publication Number US2002062334 to  
22 Hewlett Packard Company, CO, USA, entitled "Dynamic  
23 agents for dynamic service provision" teaches of dynamic



1 agents and a dynamic agent infrastructure that supports  
2 dynamic behaviour modification of agents. Dynamic agents  
3 carry out application specific actions, which can be  
4 loaded and modified on the fly. One key limitation of  
5 the approach presented is that it refers to the dynamic  
6 deployment of agent behaviour - but for the system to  
7 work as described, that dynamically deployed behaviour  
8 must be predefined (so that individual programs can know  
9 what to expect from others). The term 'dynamic' is thus  
10 misleading. The work could better be described as the  
11 dynamic deployment of statically defined behaviour. One  
12 problem presented by this aspect of US2002062334 is that  
13 software engineering in the large, and in particular,  
14 multi-party and multi-site development is made much  
15 harder by the need to conform to a rigid prespecified  
16 sets of functionality. It would be advantageous for new  
17 functionality to be definable dynamically, so that  
18 separate teams can work in greater isolation, thereby  
19 simplifying problem decomposition.  
20  
21 US2002062334 describes dynamic functionality in an agent.  
22 It does not decouple functionality and therefore does not  
23 support functionality that is not at least defined at  
24 agent start-up. It discloses that the dynamic agent's  
25 modifiable portion includes its data, knowledge and  
26 action programs, which determines its application  
27 specific capabilities. Thus the generic, fixed portion of  
28 a dynamic agent, together with its application programs,  
29 acts as an autonomous problem solver. This means that  
30 generic capabilities (such as reasoning) are fixed at the  
31 point of startup of an agent. For agents that persist  
32 over a long period (months and years, rather than hours

1 or days) this means that it is impossible to introduce  
2 new, generic capabilities as they become available.

3

4 Finally, the US2002062334 does not explain how existing  
5 functionality might be replaced. Crucially, if demands  
6 are made of a carried action, and those demands pile up,  
7 and the carried action is then replaced, there is no way  
8 of coordinating the rescheduling of those demands for the  
9 new carried action. By having a specific component  
10 responsible for handover during update, it would become  
11 possible to queue these demands until the new  
12 functionality is in a position to handle them.

13

14 Agents represent individuals, and typically persist over  
15 long periods. It is thus a very real problem that adding  
16 new generic functionality and upgrading existing  
17 functionality in deployed systems should be prohibited.  
18 As a consequence, it would be advantageous to implement a  
19 method by which even the core, generic functionality can  
20 be replaced. A portion of the data of an agent may be  
21 retained, at the discretion of the update mechanism, to  
22 maintain coherence (so, for example, the beliefs of an  
23 agent may persist through an update of core  
24 functionality). This would allow upgrading of deployed  
25 agents through a straightforward, scalable mechanism.

26

27 US2002062334 discloses that when multiple actions are  
28 carried by the same dynamic agent, they can exchange  
29 information through the object store of that dynamic  
30 agent. A first problem with this is that for a carried  
31 action to be able to use data from another module, it  
32 must be able to anticipate the availability and internal  
33 structure of that data. That is, it must have knowledge



1 of the "interface" provided by that action. So for any  
2 two actions that might need to interact, they must (a)  
3 know that the other action is carried, (b) know enough  
4 about that action to know what data it can provide and in  
5 what format. In this way, any 'old' carried action will  
6 be unable to exploit the functionality developed in 'new'  
7 carried actions that was unanticipated at the time of the  
8 development of the 'old' carried action. This is a clear  
9 theoretical problem that translates into a large  
10 practical problem in situations where agent systems are  
11 deployed on a wide basis, particularly if they are  
12 persistent, and subject to rigorous quality of service  
13 requirements (such that they can't simply be 'switched  
14 off' for an upgrade). A second problem, in a similar  
15 vein, is that old actions cannot know of the methods  
16 (i.e. published procedures) of a newer carried action. It  
17 is presumably for this reason, coupled with the fact that  
18 it is much more difficult to design all possible method  
19 interfaces on a system-wide basis at the outset, than it  
20 is data interfaces, that means that the disclosed system  
21 does not support method calls between carried actions.  
22 This reduces the potential for synergistic interplay  
23 between carried actions, and can lead to requiring  
24 redundancy (reimplementing identical functionality in  
25 different carried actions). The problem is thus that one  
26 carried action cannot make a call upon the abilities of  
27 another. This violates key principles of modern  
28 programming practice aimed at code reuse and adaptation,  
29 by forcing modules to implement all the functionality  
30 that they will need, rather than utilising functionality  
31 they may know is already available within other modules  
32 in the agent. Agentative representation in mobile  
33 services represent a domain in which persistency is

1 Preferably said method means performs said function  
2 responsive to said request.

3

4 Preferably said request from a requesting module  
5 comprises a label specifying a function and said method  
6 means in said dockable module corresponds to the  
7 specified function.

8

9 Preferably said intermodule communication means comprises  
10 a store of labels and associated modules.

11

12 Preferably said store of labels and associated modules is  
13 a table.

14

15 Optionally said method means performs the function of  
16 docking said dockable module with said agent.

17

18 Optionally said method means performs the function of  
19 registering a label with said intermodule communication  
20 means, the label specifying a function supported by said  
21 dockable module.

22

23 Optionally said method means performs the function of  
24 undocking said dockable module from an agent.

25

26 Optionally said method means performs the function of  
27 requesting the discarding of a label from the intermodule  
28 communication means, the label specifying a function  
29 supported by said dockable module.

30

31 Optionally said method means performs the function of  
32 updating said dockable module within said agent.

33

1 According to a second aspect of the present invention,  
2 there is provided a method of deployment a module in an  
3 agent comprising the steps of:

- 4     • receiving a request for deployment of said module;
- 5     • maintaining registration information relating to a  
6       function supported by said module; and
- 7     • invoking said function.

8  
9 Preferably said step of maintaining registration  
10 information comprises maintaining a store of labels and  
11 associated modules, each label specifying a function  
12 supported by a module.

13  
14 Preferably said store of labels and associated modules is  
15 a table.

16  
17 Preferably said step of maintaining registration  
18 information comprises the step of registering a label  
19 specifying a function supported by said module.  
20 This type of deployment is docking.

21

22 Alternatively said module is a docked module and said  
23 step of maintaining registration information comprises  
24 the step of unregistering a label specifying a function  
25 supported by said docked module.

26 This type of deployment is undocking.

27

28 Alternatively said module is a replacement module and  
29 said step of maintaining registration information  
30 comprises the steps of:

- 31     • unregistering a label specifying a function  
32       supported by a docked module from said agent; and

- 1       • registering a label specifying a function
- 2       supported by said replacement module with said
- 3       agent

4   and said method further comprises the steps of:

- 5       • storing information related to the state of said
- 6       docked module; and
- 7       • instantiating said replacement module using said
- 8       stored information.

9   This type of deployment is updating.

10

11   Optionally, said step of maintaining registration  
12   information further comprises the step of queuing calls  
13   to the docked modules' registered labels, prior to the  
14   step of registering a label specifying a function  
15   supported by said replacement module.

16

17   According to a third aspect of the current invention said  
18   function supported by said module according to the second  
19   aspect is the method of deployment of said module  
20   according to the second aspect.

21

22   In order to provide a better understanding of the present  
23   invention, an embodiment will now be described by way of  
24   example only and with reference to the accompanying  
25   Figures, in which:

26

27   Figure 1 illustrates, in schematic form, an agent and a  
28   module in accordance with a preferred embodiment of the  
29   present invention;

30

31   Figure 2 illustrates, in schematic form, an overview of  
32   agentative representation in a multi-service environment;

33

1 Figure 3 illustrates, in schematic form, the process by  
2 which a label is resolved in accordance with a preferred  
3 embodiment of the present invention;

4

5 Figure 4 illustrates, in schematic form, module docking  
6 in accordance with the present invention;

7

8 Figure 5 illustrates, in schematic form, module updating  
9 in accordance with the present invention;

10

11 The inventions are an architecture and methods for  
12 dynamic deployment of modules in a software agent.

13

14 Although the embodiments of the invention described with  
15 reference to the drawings comprise computer apparatus and  
16 processes performed in computer apparatus, the invention  
17 also extends to computer programs, particularly computer  
18 programs on or in a carrier, adapted for putting the  
19 invention into practice. The program may be in the form  
20 of source code, object code, a code of intermediate  
21 source and object code such as in partially compiled form  
22 suitable for use in the implementation of the processes  
23 according to the invention. The carrier may be any  
24 entity or device capable of carrying the program.

25

26 For example, the carrier may comprise a storage medium,  
27 such as ROM, for example a CD ROM or a semiconductor ROM,  
28 or a magnetic recording medium, for example, floppy disc  
29 or hard disc. Further, the carrier may be a  
30 transmissible carrier such as an electrical or optical  
31 signal which may be conveyed via electrical or optical  
32 cable or by radio or other means.

33

1 When the program is embodied in a signal which may be  
2 conveyed directly by a cable or other device or means,  
3 the carrier may be constituted by such cable or other  
4 device or means.

5

6 Alternatively, the carrier may be an integrated circuit  
7 in which the program is embedded, the integrated circuit  
8 being adapted for performing, or for use in the  
9 performance of, the relevant processes.

10

11 With reference to Figure 1, the architecture 100 of an  
12 agent according to the present invention is best  
13 visualised as including a torus. On the inside of the  
14 torus 102, a special module, the core module 104,  
15 attaches itself. On the outside of the torus, any number  
16 of application specific modules 106, 108 may also become  
17 attached. The security and unity of the agent is also  
18 conceptually protected by a thin sphere 110 encompassing  
19 all the modules. The torus itself coordinates all  
20 communication between modules and between modules and  
21 core: this is the Inter Module Communication Layer  
22 (IMCL).

23

24 The modular architecture is implemented as a class that  
25 defines a module, from which specific classes,  
26 corresponding to modules with specific functionality, can  
27 be derived. A module 112 is shown with its components  
28 depicted. The module contains a number of components for  
29 implementing functions:

30 1. A docking method 114 that is called when the  
31 module is introduced to the agent and that describes  
32 the functionality provided by that module;



11

- 1        2. An undocking method 116 that is called when the
- 2        module is required to detach itself from the agent
- 3        and terminate;
- 4        3. An update method 118 that is called when the
- 5        module is to be updated with a new version; and
- 6        4. A message handling method 120 for between-agent
- 7        communication.

8

9        The docking method of a particular module provides the

10       IMCL with a list of labels. The extensible set of these

11       labels is consistent system-wide, functioning as the

12       definition of the system's programming interface and is

13       maintained centrally by the service provider. A

14       particular module implements methods that match some

15       (typically small) subset of all labels. On docking, a

16       module informs the IMCL which labels it provides

17       functionality for. As each module docks, the IMCL builds

18       a table 122 of labels against which are listed the names

19       of the methods that provide the functionality and the

20       names of the modules implementing those methods.

21

22       In some cases, the labels implemented by a particular

23       newly docking module may already be implemented by

24       methods extant in the agent. So for example functionality

25       f implemented by method x in module m1 may mean that when

26       m1 docks in an agent, it needs to register the label f

27       with the IMCL. But some other method, y, in some other

28       module, m2, that is already docked, may also implement

29       functionality f. Thus the IMCL would list functionality

30       f as being implemented by m2.y.

31

32       In such situations, the IMCL adds the new label and

33       associated method to its table, but also includes a

12

1 priority ranking, applied to both the new and old methods  
2 that implement the functionality. This priority is  
3 determined on the basis of some algorithm. Recency is a  
4 good example, whereby newer methods are always given a  
5 higher priority, but there are many such algorithms.  
6  
7 In addition, a module's docking method calls functions  
8 provided by the core's module management. These calls  
9 register information about the module with the core,  
10 including its name, provenance and labelled  
11 functionality. The processes of docking and module  
12 updating are described below with reference to Figures 7  
13 and 8.  
14  
15 A user interacts with the electronic world for a host of  
16 reasons in a wide variety of domains: entertainment, e-  
17 commerce, professional, and so on. The present invention  
18 provides a means of bringing together all of these tasks  
19 and domains, and providing a single point of contact for  
20 the user, and allowing the sharing of user data between  
21 these different application domains. This contact is the  
22 user's agent, both in the computer-science sense (where  
23 agent oriented programming has particular restrictions,  
24 techniques and approaches, and places particular demands  
25 on software), and also in the intuitive sense of  
26 providing services of advocacy and representation. A  
27 user's agent is their permanent representative in the  
28 electronic world. Ideally, each user has exactly one  
29 agent, and a user's agent represents exactly one user (at  
30 the very least, such a relationship exists in a given  
31 context). The overall picture is as in Figure 2.  
32

1 With reference to Figure 2, an overview of agentative  
2 representation in a multiservice environment is shown.  
3 The user 202 connects to their agent 206 at any time via  
4 any device (2G phones, multimedia mobile handsets,  
5 internet, etc.) in ways that are well known. The user  
6 agents 204 which represent users in the virtual world are  
7 shown. One user has a single agent 206 representing him  
8 or her in all their interactions in the virtual world.  
9 The service agents 208 provide specific services to any  
10 agents that request them, or that the service agents  
11 themselves decide to service. Information exchange  
12 between user and service agents can be initiated from  
13 either end. Some service agents 210 encapsulate existing  
14 legacy services (e.g., databases, Web Services and  
15 proprietary data handling systems). Broker agents 212  
16 can mediate between a user and service agents. The user  
17 agents service agents and broker agents may be provided  
18 as a trusted service by a telecommunications operator.  
19  
20 An agent is a software entity with particular  
21 characteristics. We refer here to software processes that  
22 are:  
23 (i) persistent (in that they continue to exist for an  
24 extended real time period, adapting to a single user  
25 over that time);  
26 (ii) proactive (in that they include not only reactive  
27 behaviour, but also independently determined  
28 behaviour);  
29 (iii) communicative (in that they communicate with  
30 other agents); and  
31 (iv) autonomous (in that they typically cannot be  
32 directly modified by outside agencies, but must  
33 instead be altered through communication).

14

1  
2 The user can communicate with his agent across  
3 heterogeneous networks from a variety of devices,  
4 including mobile handsets and internet clients. In  
5 addition, however, the framework of the present invention  
6 supports the transparent filtering of information  
7 according to the device to which it is being sent. Thus  
8 the components within an agent that initiate  
9 communication with a user need not have any  
10 representation of the device type a user is employing.  
11 The content of the message is instead dynamically  
12 tailored to the user's device (e.g. summary text to an  
13 SMS-enabled mobile device, still pictures to a MMS-  
14 enabled mobile device, streaming video to broadband  
15 internet client platform, etc.).  
16  
17 The core is responsible for tailoring information to the  
18 device that is known to currently be available to the  
19 user. Thus, tailoring happens independently of the  
20 module calls, so that individual modules do not need to  
21 maintain device-specific information.  
22  
23 This filtering is achieved through a module-independent  
24 communication object that is filled in by individual  
25 modules when they need to communicate with the user.  
26 This object has subparts for different forms of media  
27 (text, picture, video, audio, etc.,). A module fills in  
28 as many of these subparts as it is able. The core then  
29 mediates the sending of that message to the user, by:  
30 (i) identifying which device the user is currently  
31 employing (using a combination of historical usage  
32 patterns, presence information, and most recent-  
33 communication data);

1 User data (e.g., address; credit card details; age) and  
2 user preferences (e.g., policy on releasing credit card  
3 details; preference for aisle or window seat on planes;  
4 preferred DVD supplier) are stored in a local, private,  
5 secure database. Both user data and user preferences are  
6 extracted in three ways. First, through an explicit  
7 online interface that requests input on date of birth, or  
8 supports update to reflect change of address. Second, if  
9 the agent recognises information that it needs from the  
10 user, it can ask for it directly (e.g. asking a yes/no  
11 question by SMS). Third, as the user interacts with  
12 services manually, the agent can intercept information  
13 either explicitly or implicitly. If the user answers a  
14 particular question from a particular online service, the  
15 agent may either store that answer for future use, or ask  
16 the user explicitly if such storage is appropriate or  
17 useful. When acting autonomously, the agent provides  
18 information that external service requires (and no more),  
19 less anything that the user has placed a restriction on.  
20 Thus, for example, when interacting with an online  
21 newspaper, the newspaper provider may request user  
22 registration, but not demand it. In this case, the agent  
23 would provide no user information. Alternatively, when  
24 interacting with a book e-tailer, the e-tailer may  
25 require personal details including credit card data. If  
26 the user has instructed his or her agent not to give out  
27 credit card details without confirming it first, the  
28 agent would halt interaction with that site until user  
29 confirmation was sought and agreed.

30

31 These components could be represented by the steps:

32 1. Agent has goal of interacting with a service



18

1           2. Select required information from the user model  
2           (UM) (accesses the UM)  
3           3. Check that the user model permits all this  
4           information to be freely given (accesses the UM)  
5           If so,  
6           4. Information given to the service  
7           Otherwise  
8           5. Process the restriction (either by terminating,  
9           or by asking the user, or by performing some  
10          other action)  
11  
12       The core also includes a subsystem responsible for  
13       passing messages to, and receiving messages from the  
14       user. The user may connect to his or her agent through a  
15       number of different channels: using a web browser on a  
16       PC, using a rich media mobile device (a Java phone, for  
17       example), using a high capacity mobile device (such as  
18       one that uses GPRS), or using an older, limited media  
19       device (say that can only handle voice and SMS traffic).  
20       The core implements labels that handle communication to  
21       and from such devices quite transparently: the calling  
22       module does not need to specify the different  
23       communication types at all.  
24  
25       The means by which one agent communicates with another is  
26       implemented in the core. Rather than supporting only  
27       agent-to-agent messages, the architecture is instead  
28       built around the idea that it is individual modules  
29       within agents that communicate with one another (this is  
30       "between agent module-module" or BAMM communication).  
31       Thus a module with expertise in buying in a particular e-  
32       commerce institution will communicate with a module in  
33       another agent that has expertise in selling in that same



22

1 labels with the IMCL and initialise 728 the BAMM handler  
2 before ending the process 730.

3

4 The undocking method of a particular module informs the  
5 IMCL and the core module management that the  
6 functionality provided by the module is terminating, and  
7 then kills the module's thread.

8

9 One of the advantages of decoupling of functionality in  
10 separate modules is in allowing modules to be added to an  
11 agent on-the fly. Such modules need not have  
12 functionality that is known before the agent is  
13 instantiated, as each module describes its own behaviour  
14 and functionality on docking. The same approach can be  
15 used to update existing modules with new versions.

16

17 Another, practical, advantage of the approach is that it  
18 removes compile time dependencies: a module developer can  
19 design, implement and test a module which makes calls to  
20 another module that they do not have, or do not have  
21 access to, or, indeed, that has not been developed at  
22 all. This simplifies many of the problems of software  
23 engineering in the large, and of multi-site collaborative  
24 development work.

25

26 The core is responsible for the handling of new modules  
27 and module updates. It arranges for outgoing requests to  
28 be sent for new modules (or for updated versions of  
29 existing modules), handles incoming requests for the  
30 agent to take on new modules, and handles the process by  
31 which a module is added. So, for example, if the user  
32 decides to sign up for a new, free service, the core may  
33 send a message to the coordinating agent for that

1 service, requesting the module. After some brief  
2 negotiation, the coordinating agent may send back a  
3 request to install the new module. The core module  
4 management accepts and downloads the software. After  
5 updating the internal module database, it starts the new  
6 module, which then docks with the IMCL, as described  
7 above.

8  
9 The process of updating a module and the handover between  
10 the older and newer versions is illustrated in Figure 5.  
11 With reference to Figure 5, a flowchart 800 of the module  
12 updating process is shown. First, either a user specifies  
13 802 a module, the core receives a message 804 specifying  
14 a module to update, or the core determines 806 that a  
15 module should be updated. The core reasons and decides  
16 808 whether or not to update the module. If an update is  
17 determined to be completed, the core calls 810 the IMCL  
18 with the getmodule label and URI specifying the location  
19 of the Java Archive file. If not, the updating process  
20 ends 836. The IMCL then resolves 812 updatemodule label  
21 to the ModuleManagement.ModuleUpdate method in the core  
22 and the IMCL calls 814 the core's  
23 ModuleManagement.ModuleGet method with the module name  
24 and the URI. ModuleManagement calls 816 the module's  
25 UpdateMe method and the UpdateMe method returns the  
26 module state information, which is then stored 818 by  
27 ModuleManagement. ModuleManagement downloads 820 the Java  
28 Archive file from the URI. The .jar manifest file 822  
29 specifies the Module class and the Module class 824  
30 includes the DockMe method. With this information, the  
31 ModuleManagement instantiates 826 the Module class and  
32 calls 828 the DockMe method with the stored state  
33 information. The DockMe method may then register 830

1 labels with the IMCL and initialise 832 the BMM handler  
2 before the Module Management calls 834 the UnDockMe  
3 method on the old module and unloads the class then ends  
4 the process 836.

5

6 The core's module management also handles more complex  
7 situations, in which a new version of an existing module  
8 is installed. The handover between the modules requires  
9 careful timing to ensure service to the rest of the agent  
10 are not disrupted. When a new version of a module is to  
11 be docked, the core module management calls the old  
12 version's update method, and, at an appropriate moment  
13 (at a break between discrete tasks that the module is  
14 working on) the module returns a representation of its  
15 current state.

16

17 Then, as part of the new module's docking method, it  
18 accepts the state of the previous version's data, so that  
19 it can pick up from where the previous module left off.

20

21 During the handover between versions of a module, the  
22 IMCL queues calls to the modules' labels, awaiting the  
23 docking of the new version.

24

25 Some of the functionality described herein is collected  
26 together in the core. Rather than hardwire a distinction  
27 between core and other modules, the core is instead  
28 implemented in just the same way as any other module.  
29 This means that calls on core functionality can exploit  
30 the robustness of the label-based, IMCL-mediated method  
31 calling.

32


25

1 It also means that core itself can be updated and docked  
2 through just the same process as any other module (so the  
3 activity of the module management component in the old  
4 core is interrupted and then taken up by the activity of  
5 the module management component in the new core). This  
6 means that new core functionality can be deployed  
7 dynamically, without other modules needing to know ahead  
8 of time all that might be included.

9

10 Further modifications and improvements may be added  
11 without departing from the scope of the invention herein  
12 described.

13



1/5




Fig. 1





2/5




Fig. 2



3/5




Fig. 3



4/5




Figure 4





5/5




Figure 5

